



Energy-Saving Refrigeration Dryers

SECOTEC® TE, TF and TG Series

Efficient, compact and maintenance-friendly

Flow rate 10.5 to 98 m³/min, Pressure 3 to 16 bar

Compact, energy-saving refrigeration dryers with impressive latent heat storage

KAESER’s renowned industrial-quality SECOTEC series refrigeration dryers have long been valued for their stable pressure dew point performance, exceptional reliability and low life-cycle costs. Now, the enhanced second generation offers even greater efficiency with a more compact design and further-optimised user-friendliness, thanks to such features as: the compact SECOPACK LS heat exchanger system with its high-efficiency latent heat storage, the standard-equipped, network-capable SIGMA CONTROL SMART controller and the innovative exhaust air control fitted to air-cooled refrigeration dryers from 45 m³/min. Furthermore, with the climate-friendly refrigerant R-513A, KAESER assures security of supply for the future.

Energy cost savings

SECOTEC refrigeration dryers require less than 100 W of electrical power per m³/min of compressed air (as per ISO 7183 A1). Thanks to its energy-saving control, surplus cooling performance can be stored temporarily in the thermal mass during partial load operation and subsequently used for drying, without the need for additional energy consumption. The rapid-reaction SECOPACK LS heat exchanger system ensures stable pressure dew points at all times.

Optimised and compact


The thermal mass storage in the highly efficient SECOPACK LS heat exchanger system is filled with a phase change material which, thanks to its significantly higher thermal storage density, requires 98% less storage material to achieve the same capacity as conventional storage media. This not only ensures excellent pressure dew point stability, but also drastically reduces the footprint of the unit. Optimised flow paths minimise pressure losses, thereby helping to enhance the efficiency of SECOTEC dryers.

Intuitive operation

The electronic SIGMA CONTROL SMART controller with colour display and language-neutral menu navigation is simple and intuitive to operate. Message memory, component-specific operating hour counters and maintenance timers enable efficient monitoring and analysis of operational data. Floating contacts and a Modbus TCP communications module provide easy networking with master controllers, such as the SIGMA AIR MANAGER 4.0.

Long-term reliability

The high-performance refrigerant circuit in SECOTEC refrigeration dryers assures reliable performance in ambient temperatures up to 50 °C. The large condensate separator and electronic ECO-DRAIN condensate drain provide reliable condensate removal during all load phases. Long service life is assured through the use of aluminium for the condenser and SECOPACK LS, whilst the compressed air piping is constructed from stainless steel. The innovative exhaust air control fitted to the SECOTEC TG reliably conveys away the exhaust heat, ensuring efficient and long-lasting operation.



Reduce life-cycle costs!

Three factors are responsible for achieving the exceptionally low life-cycle costs associated with SECOTEC refrigeration dryers, namely: low-maintenance system design, energy-efficient components and, above all, the demand-dependent SECOTEC energy-saving control.

This triple combination enables a SECOTEC TF 340, for example, to achieve life-cycle cost savings of up to 50% when compared to other refrigeration dryers typically available on the market.

Example: SECOTEC TF 340

Flow rate 34 m³/min, 40 % load, 6.55 kW/(m³/min), extra energy demand 6 % per bar, 0.20 €/kWh, 6,000 operating hours per year, annual debt service over 10 years.

Efficient, compact, maintenance-friendly



Image: SECOTEC TF 340



KAESER

SECOTEC TE 142

CF 9

SECOTEC® TE, TF and TG Series


Energy-efficient powerhouses

Consistent use of high-quality components and our decades of experience in system design enable SECOTEC refrigeration dryers to achieve world-class energy efficiency – across the entire load range.



Efficient refrigerant compressor

The scroll refrigerant compressors used in SECOTEC dryers are up to 26% more efficient than reciprocating compressors. They therefore play an important role in ensuring the outstanding efficiency of KAESER refrigeration dryers.



Minimal differential pressure

Second generation SECOTEC refrigeration dryers stand out for their remarkably low differential pressure. This is a result of the generously-dimensioned flow cross-sections within the heat exchanger and compressed air connection lines.



Efficient thermal mass

The efficient phase change material gives the exceptionally compact SECOPACK LS heat exchanger system its impressive thermal mass storage capacity. Special heat transfer elements ensure rapid charge and discharge, whilst premium-grade heat insulation boosts efficiency even further.



Significant energy savings

The SIGMA CONTROL SMART controller calculates the new SECOTEC dryer's load hours and current actual power consumption. This advanced system also displays the savings achieved as compared to conventional hot gas bypass refrigeration dryers.

Reliable drying

We do not just talk about challenging operating conditions, but actually create them using our advanced climate testing facilities. This allows us to fine-tune the design of SECOTEC refrigeration dryers in order to ensure maximum reliability at all times.



Controlled availability

The innovative SIGMA CONTROL SMART controller regulates the operation of the thermal mass whilst constantly monitoring system temperature and pressure values. Automatic wire break and short circuit monitoring add even greater operational security.



Compact condenser

Aluminium micro-channel condensers with large surfaces ensure effective contamination reserve, whilst their compact design saves both space and refrigerant quantities. This enables SECOTEC refrigeration dryers to deliver reliable drying performance even at high ambient temperatures.



Reliable separation

The SECOPACK LS heat exchanger system is made of corrosion-resistant aluminium and includes an integrated, large-diameter condensate separator for reliable separation of condensate during all load phases.



Future-proof refrigerant

The refrigerant circuit in SECOTEC refrigeration dryers is specifically designed for the use of R-513A refrigerant. This ensures maximum efficiency and reliability, even at the highest temperatures, whilst providing the best solution currently available for the security of your future supplies.

Dependable
performance
up to

50 °C

ambient
temperature



Easy installation and excellent accessibility

KAESER understands our customers' needs very well, as the company itself operates numerous compressed air stations. From first-hand experience, we are well-versed in all aspects of compressed air station planning, commissioning, operation and maintenance. We draw on this expertise to create user-friendly products with minimal need for maintenance.



Left-hand side compressed air connections (optional)

If required, SECOTEC TF refrigeration dryers are available with compressed air connections located at the top of one side. This customised solution enables rapid installation at low cost.



Externally accessible: ECO-DRAIN

The standard-equipped ECO-DRAIN electronic condensate drain is conveniently located on the exterior of the unit, where it is easily accessible for functional testing. The service unit can be replaced without depressurisation of the refrigeration dryer by simply closing the condensate inlet valve beforehand.

SECOTEC – The ultimate space-saver

TE and TF series...



...with two wall sides

SECOTEC TE and TF series units can be installed against walls on two sides, leading to even further space savings.

TE and TF series...



...the compact duo

Where multiple energy-saving refrigeration dryers are required, SECOTEC TE and TF series units can easily be installed together as a compact duo.



Image: SECOTEC TF 340 (left), SECOTEC TG 780 (right)

Quick maintenance access

On SECOTEC TE and TF series units, removable panels allow easy access to all maintenance components. On TG series units, maintenance access is provided via large doors. The micro-channel condenser is also easily accessed for cleaning.

TE, TF and TG series...



...back-to-back

Two energy-saving refrigeration dryers and not much space? No problem! TE, TF and TG series refrigeration dryers are equipped for back-to-back installation.

TG series...



...with just one wall side

The SECOTEC TG series combines maximum performance with a minimum need for space. Even installation against the wall on just one side poses no problem.

SIGMA CONTROL SMART

Comprehensive information and intuitive operation

The new generation of SECOTEC refrigeration dryers is equipped with the SIGMA CONTROL SMART electronic controller. With its colour display and language-neutral menu navigation, this advanced controller is exceptionally user-friendly.

Operational status can be viewed at a glance via the dew point trend indicator, prominent display of active messages and current operating data, as well as a clearly arranged P&I diagram. Furthermore, a message memory and floating message contacts, together with the standard-equipped network interface, provide highly effective analysis and monitoring capability. All information can be communicated to a master controller via the SIGMA NETWORK.




Main menu

- Pressure dew point trend display
- Eco-symbol displayed when thermal mass activated
- List of additional menus, symbols: Controls for voltage, fault, warning/maintenance, remote on/off, controller on
- Status indicator for component-specific messages
- Flagging of pending maintenance/warning and affected component
- Faults requiring action indicated in red


SECOTEC TF 340

KAESER




Messages

- Maintenance/warning: indicated in orange
- Faults: indicated in red
- Unacknowledged message: indicated by a border
- Messages identifiable by numerical codes
- Messages timestamped with operating hours
- Counter shows number of past messages




Information

- Multiple operating hour counters
- Temperature thresholds for messages
- Activation of remote on/off
- Display of actual electrical power consumption
- Estimated energy savings compared to dryers with hot gas bypass control
- Change measurement units



P&I diagram

- Displays functional principle
- Messages displayed with coloured switch symbols (e.g. condensate drain maintenance)




Service

- List of individual maintenance intervals for condensate drain and condenser cleaning
- Current interval status
- Reset maintenance timer

Innovative energy-saving control with Storage Plus

For its Storage Plus energy-saving control, KAESER uses a special phase change material that absorbs latent heat. In contrast to other thermal mass storage systems available on the market, the heat energy does not go through a temperature change; rather, it goes through a phase change. Only when the entire medium has undergone

this phase change - meaning that the storage is now full - does the temperature begin to rise. When the latent heat is discharged, the phase change reoccurs in the opposite direction, with the temperature remaining constant until all the heat has been discharged.



- (1) Refrigerant compressor runs: Cooling is supplied for drying the compressed air and cooling down the thermal mass.
- (2) Thermal mass solidifies at constant temperature and transfers a significant amount of heat to the refrigerant.
- (3) Refrigerant cools the thermal mass down further until the cut-out temperature is reached.
- (4) Refrigerant compressor switches off.
- (5) Thermal mass provides cooling for drying the compressed air and, in doing so, warms up.
- (6) Thermal mass melts at constant temperature, taking on a significant amount of heat from the moist compressed air.
- (7) Thermal mass warms up to the cut-in temperature of the refrigerant compressor.

Modbus TCP communications module

SECOTEC – Industrie 4.0 ready

With their standard-equipped Modbus TCP module, SECOTEC refrigeration dryers can be connected to the SIGMA AIR MANAGER 4.0 and the SIGMA NETWORK. All essential operational parameters and messages are available in real-time, enabling comprehensive monitoring of the entire compressed air station and creating the basis for preventative maintenance based on need. The result:

maximum air availability for minimal cost. Furthermore, the SIGMA AIR MANAGER 4.0 provides a complete overview of all of the refrigeration dryer's essential operating parameters. Colour-coded warnings and alarms are displayed in the compressed air station's P&I diagram. By selecting the dryer icon, all key operational parameters and message texts are displayed in plain text.

SIGMA AIR MANAGER 4.0

Station: Station
Power: 128.50 kW
Flow rate: 24.55 m³/min
6.62 bar
Automatic

D1 - TE 102

Model: TE 102

Electrical power consumption: 0.87 kW
Pressure dew point: **Normal**
Warning limit, yellow range: 14.0 °C
Warning limit, red range: 20.0 °C

Automatic restart: Yes
Remote control: No

Operating hours: 10598 h
Remaining maintenance hours, Condensate drain: 1374 h
Remaining maintenance hours, Condenser cleaning: -17 h
Group warning: No
Group alarm: No

"Condenser cleaning" maintenance due

SIGMA AIR MANAGER 4.0

SIGMA CONTROL SMART

Networked compressed air station

SECOPACK LS heat exchanger system


The high-efficiency module for maximum energy savings

Second generation SECOTEC refrigeration dryers are equipped with the innovative SECOPACK LS heat exchanger system. Its latent heat thermal mass is composed of a phase change material. Compressed air warms the material up to its melting point (thermal mass discharge), absorbing melt heat during the process. This is significantly more than the amount of heat that it can absorb based on its normal specific heat capacity (without the phase change properties), so the latent heat thermal mass in SECOTEC dryers has a dramatically higher thermal density than equivalent conventional systems and is therefore capable of delivering the same performance using 98% less thermal mass material.

The result: High thermal mass storage capacity for stable pressure dew points and long-life operation, combined with a dramatically reduced unit footprint.





Image: SECOPACK LS in SECOTEC TF




Design


- (1) Compressed air inlet
- (2) SECOPACK LS heat exchanger system
- (3) Compressed air outlet
- (4) Condensate outlet
- (5) ECO-DRAIN condensate drain
- (6) Refrigerant compressor
- (7) Micro-channel condenser
- (8) Fan
- (9) Filter dryer
- (10) Refrigerant collector
- (11) Expansion valve




Air/air heat exchanger



Air/refrigerant heat exchanger



Condensate separator



Thermal mass (yellow section)

Image: SECOPACK LS

SECOTEC TG Series

SECOTEC TG - Compact giants

SECOTEC TG series energy-saving refrigeration dryers can accommodate flow rates up to 98 m³/min and are available with a choice of air or water-cooling. Designed for large-scale industry, these compact giants ensure stable pressure dew point performance even under the toughest of operating conditions - with maximum reliability and minimal life-cycle costs.

The high-performance thermal mass concept and standard, network-capable SIGMA CONTROL SMART controller guarantee long-lasting, energy-saving operation in all load phases. The innovative exhaust air control, fitted on air-cooled variants, sets new standards for operational safety and cost efficiency.



Innovative exhaust air control

Dependent on load, the frequency-controlled radial fan draws off the accumulating exhaust heat from the refrigeration dryer via the cooling air flow. Thanks to a residual thrust of 150 Pa and autonomous control, direct connection to standard exhaust and collector ducting is possible.



Thermal mass concept with multiple compressors

The SECOPACK LS heat exchanger system with latent heat thermal mass operates in combination with up to three refrigerant compressors arranged in parallel. These are switched continuously according to the load level, thereby relieving the load on the thermal mass, allowing it to be made even more compact.



Reduced operator responsibilities

Thanks to its compact components, the SECOTEC TG operates using particularly low levels of refrigerant charge. Low greenhouse gas potential also ensures cost-effective compliance with national operator regulations. Furthermore, there is no need to perform the leak tests required under the European F-gas regulations (EU 517/2014). However, it is still recommended to have the unit inspected once per year by a certified expert.



Minimal service costs

The condensate separator in the SECOPACK LS does not require servicing. It is just a matter of replacing the service unit in the standard ECO-DRAIN condensate drain - no further maintenance work is required. Unlike typical axial fans, the radial fans in the SECOTEC TG are designed to last for the unit's entire service life.



KAESER

SECOTEC

TG780

MADE IN GERMANY



Image: Cooling air flow (red) on SECOTEC TG units

SECOTEC TG Series

Your **benefits** compared to previous models, at a glance

No risk of thermal overload

Refrigeration dryers are usually supplied without a dedicated exhaust air duct. The result is thermal overload - caused by hot exhaust air being drawn back in as cooling air. However, the innovative exhaust air control on the SECOTEC TG, coupled with its direct connection to the exhaust air duct, reliably prevents this issue from occurring.

No unwanted air intake, no auxiliary fan

In the case of conventional ventilation systems, which use air hoods and auxiliary fans, air from the room is invariably drawn in. This is not so with the SECOTEC TG: the exhaust air flow is minimised, which means smaller ducting can be used and the auxiliary fan becomes redundant.

Innovative exhaust air control

Its innovative exhaust air control allows the SECOTEC TG to be connected directly to the compressor station; the resulting significant space-savings reduce planning and installation costs. Optimal cooling also serves to ensure stable pressure dew points and long-lasting, energy-saving operation.





Image: Example air station with collector duct for compressors and refrigeration dryer

The key to perfect refrigeration drying



SECOTEC – Savings for all seasons

The load on a refrigeration dryer depends not only on the volume of compressed air to be dried (grey area), but more importantly, on how much water the incoming compressed air contains. This volume of water (moisture) increases as the temperature rises, so the load on refrigeration dryers increases dramatically when ambient temperatures are high, such as during the summer (yellow curve).

Lower temperatures during the winter (teal blue curve) therefore reduce the load on refrigeration dryers accordingly. To maintain a stable pressure dew point throughout all these fluctuations, refrigeration dryers should always be designed to provide sufficient performance during peak load times, and should also have additional capacity in reserve.


Aside from these fluctuations in air flow and temperature, the output of refrigeration dryers constantly varies between 0 and 100 % of capacity. Because the SECOTEC thermal mass control ensures energy is only used as and when needed across the entire load range, users benefit from exceptional savings.

Maximum energy savings thanks to thermal mass control

Refrigeration dryer load constantly fluctuates between 0 and 100%. Unlike conventional partial-load control systems, SECOTEC thermal mass control precisely adjusts electrical power consumption during all load phases.

This allows SECOTEC refrigeration dryers to save almost 60% of energy costs compared to refrigeration dryers with hot gas bypass control running at an average of 40% of capacity. **The TF 340 model typically saves 20,000 kWh/year based on 6,000 operating hours.** In contrast to conventional systems, the thermal mass in SECOTEC dryers always remains cool.

Electrical power consumption under nominal conditions



This means compressed air can be dried effectively even during start-up phases. The high-quality insulation around the thermal mass also helps keep energy usage to a minimum. Compressed air drying with SECOTEC refrigeration dryers not only ensures exceptional energy efficiency, but also, thanks to their impressive thermal capacity, provides low-wear operation.


Optimal drying with low-wear operation

SECOTEC refrigeration dryers efficiently maintain pressure dew points of up to +3°C during full load operation. Thanks to their narrow fluctuation range, pressure dew points are also more stable during partial load operation than is the case with conventional refrigeration dryers.

In conventional refrigeration dryers with switching operating modes but no additional thermal mass, the heat exchanger material itself is used as the thermal mass. In these dryers it is therefore necessary to switch the refrigerant compressors and fan motors on and off much more frequently, in order to maintain the required cooling performance.

To reduce switching frequency and wear, the refrigerant circuit therefore only switches on at much higher pressure dew points. The resulting fluctuations in the pressure dew point negatively affect drying performance. This can be risky, since corrosion can take hold even with relative compressed air humidity of 40% – meaning that corrosion can occur even without condensate formation.

Pressure dew point in °C



SECOTEC refrigeration dryers, on the other hand, ensure long-life operation thanks to their high thermal mass storage capacity. Once the thermal mass has been charged, the refrigerant compressor and fan motor can remain switched off for much longer without impacting pressure dew point stability.

Standard equipment

Refrigeration circuit

Refrigeration circuit comprising up to three scroll compressors, aluminium micro-channel condenser with fan, pressure monitor, filter dryer, refrigerant collector, thermostatic expansion valve, SECOPACK LS aluminium heat exchanger system and pressure transducer.

SECOPACK LS

Air/air and air/refrigerant heat exchanger with aluminium block design, integrated thermal mass sector with phase change material, condensate separator, heat insulation and temperature transducer.

SIGMA CONTROL SMART

Electronic controller with colour display, language-neutral menu navigation, dew point trend indicator, P&I diagram with current operating data and messages, message memory, operating hour counter and maintenance timer.

Enclosure

Powder-coated enclosure. Removable side panel (TG series: door) for easy electrical connection and efficient cleaning of the condenser. Removable side panel (TG series: side doors) serves as main access point to the interior. Machine feet.

Condensate drainage

ECO-DRAIN 31 Vario electronic condensate drain with ball valve on the condensate inlet line, incl. insulation of cold surfaces.

Floating contacts

Messages: "Fault", "Warning / maintenance", "Pressure dew point warning". Operational messages: "A refrigerant compressor is running" plus access for "Remote On/Off".

Connections

Compressed air pipework constructed from corrosion-resistant materials. Bulkhead for connection of the external condensate line and cable bushing for mains power connection on rear wall.

Electrical equipment

Electrical equipment and testing as per EN 60204-1 "Safety of machinery". Control cabinet IP 54 protected.

Modbus TCP communications module

With the communications module, SECOTEC refrigeration dryers can be integrated into the SIGMA NETWORK or connected to a central control system.

Calculating flow rate

Correction factors for deviating operating conditions (flow rate in m³/min x k...)

Gauge working pressure at dryer inlet														
p bar _(g)	3	4	5	6	7	8	9	10	11	12	13	14	15	16
k _p (TG 980)	0.64 (0.50)	0.75 (0.63)	0.84 (0.75)	0.92 (0.88)	1.00	1.05	1.09	1.12	1.16	1.19	1.22	1.24	1.26	1.27

Compressed air inlet temperature T _i							
T _i (°C)	30	35	40	45	50	55	60
k _{Ti} (TG 980)	1.19 (1.0)	1.00	0.80	0.66	0.51	0.43	0.35

Ambient temperature T _a						
T _a (°C)	25	30	35	40	45	50
k _{Ta}	1.00	0.96	0.92	0.88	0.85	0.80



Example:			
Working pressure:	10 bar _(g)	(See table)	k _p = 1.12
Compressed air inlet temperature:	40 °C	(See table)	k _{Ti} = 0.80
Ambient temperature:	30 °C	(See table)	k _{Ta} = 0.96

TF 340 refrigeration dryer with 34.0 m ³ /min flow rate	
Max. possible flow rate under operating conditions	
$V_{\text{max Operation}} = V_{\text{Reference}} \times k_p \times k_{Ti} \times k_{Ta}$	
$V_{\text{max operation}} = 34.0 \text{ m}^3/\text{min} \times 1.12 \times 0.8 \times 0.96 = 29.25 \text{ m}^3/\text{min}$	

Technical specifications

Model		Serie TE			Serie TF				Serie TG				
		TE 102	TE 122	TE 142	TF 174	TF 230	TF 280	TF 340	TG 450	TG 520	TG 650	TG 780	TG 980
Flow rate	m ³ /min	11,5	12,5	15,5	17,0	23,0	28,0	34,0	45	52	65	78	98
Pressure loss, refrigeration dryer	bar	0,11	0,13	0,14	0,13	0,15	0,19	0,17	0,14	0,19	0,12	0,17	0,25
Elect. power consumption at 50% flow	kW	0,50	0,52	0,77	0,79	0,97	1,11	1,29	1,55	1,85	2,02	2,48	3,61
Elect. power consumption at 100% flow	kW	1,08	1,12	1,51	1,61	2,20	2,45	2,87	3,28	3,89	4,83	5,88	9,82
Gauge pressure	bar	3 to 16			3 to 16				3 to 16		3 to 13		
Ambient temperature	°C	+3 to +45			+3 to +45				+3 to +50				
Max. compressed air inlet temperature	°C	+60			+60				+60				
Mass	kg	229	230	249	345	375	395	420	637	658	704	700	763
Dimensions W x D x H	mm	712 x 982 x 1612			835 x 1230 x 2000				1025 x 1656 x 2127				
Compressed air connection		G 2			DN 65	DN 80			DN 100		DN 150		
Condensate drain connection		G ¼			G ¼				G ¼				
Power supply		400 V / 3 Ph / 50 Hz			400 V / 3 Ph / 50 Hz				400 V / 3 Ph / 50 Hz				
Refrigerant type		R-513A			R-513A				R-513A				
Global warming potential (GWP)		631			631				631				
Refrigerant mass	kg	1,50	1,55	1,55	2,80	2,90	3,40	4,50	4,30	4,35	6,40	6,00	7,90
Refrigerant mass as CO ₂ equivalent	t	0,95	0,98	0,98	1,77	1,83	2,15	2,84	2,71	2,74	4,04	3,79	4,98
Optionen													
Water-cooled version		Not available			Optional				Optional				
Adjustable machine feet		Optional			Optional				Optional				
Integrated transformer to accommodate various mains voltages		Optional			Optional				Not available				
Ambient temperature to +50 °C		Optional			Optional				Standard				
Compressed air connections on left side		Not available			Optional				Not available				
Special colour (RAL)		Optional			Optional				Optional				
Silicone-free version (VW factory standard 3.10.7)		Optional			Optional				Optional				

Performance data for reference conditions to ISO 7183, Option A1: Reference point: 1 bar(a), 20 °C, 0 % relative humidity; pressure dew point +3 °C, operating point: 7 bar working gauge pressure, compressed air inlet temperature 35 °C, 100 % relative humidity, cooling air inlet temperature 25 °C. Contains fluorinated greenhouse gas.



The world is our home

As one of the world's largest compressed air system providers and compressor manufacturers, KAESER KOMPRESSOREN is represented throughout the world by a comprehensive network of branches, subsidiary companies and authorised partners in over 100 countries.

With innovative products and services, KAESER KOMPRESSOREN's experienced consultants and engineers help customers to enhance their competitive edge by working in close partnership to develop progressive system concepts that continuously push the boundaries of performance and compressed air efficiency.

Moreover, the decades of knowledge and expertise from this industry-leading system provider are made available to each and every customer via the KAESER group's global computer network.

These advantages, coupled with KAESER's worldwide service organisation, ensure that every product operates at the peak of its performance at all times and provides maximum availability.



EMINENT POWER ENGINEERING PVT LTD
Regd. Office : 871/B1/D, GIDC Industrial Estate,
Near Himalaya Char Rasta, Makarpura, Vadodara-390 010.
Ph : +91 9824459599, Email : info@eminentpowerepl.com,
Website : www.eminentpowerepl.com